

Pro PA



Magnat



Magnet Pro PA 212



Magnet Pro PA 112



BESONDERHEITEN

- Professioneller Beschallungslautsprecher
- Stabiler Gehäuseaufbau aus 19mm MDF, robuste Schutzecken und resonanzarmes Schutzgitter
- Druckkammer Hochtontreiber mit 1.5“-Membran und angeflanschten 90°/40° Horn
- Hochbelastbarer Langhub Tieftöner mit verstärkter Papiermembran und kräftigem Magnetsystem
- Hochbelastbare Frequenzweiche
- Extra stabile und resonanzarme Tragegriffe
- Anschlußterminal mit Schraubklemmen und 6.3mm Klinkenbuchse
- Strömungsoptimierte Bassreflexöffnungen

HIGHLIGHTS

- Professionell PA speaker
- Stable 19mm MDF cabinet, rugged protection edges and resonance-free metal grill
- 1.5“ (38mm) compression horn tweeter
- Longthrow woofer-midrange with reinforced papercone and high power magnetsystem
- Highly efficient crossover
- Extra stable and low resonant carry handles
- Speaker terminal with screwterminal and 6.3mm plug
- Airflow optimized bassreflex ports

Technische Daten/Specifications

Prinzip Principle	2 – Wege Baßreflex 2 – way, bass reflex
Bestückung Equipment	1x 12“ (30 cm) Tief-Mitteltöner, 1.5“ DruckkammerHochtonhorn
Equipment	1x 12” woofer-midrange, 1.5” Compression-Horntweeter
Belastbarkeit (RMS/Max.) Power Handling (RMS/Max)	250 / 600 Watt(s) 250 / 600 Watt(s)
Impedanz Impedance	4-8 Ohm(s)
Frequenzbereich Frequency Response	30 – 22.000 Hz 30 – 22.000 Hz
Übergangsfrequenz Crossover Frequencies	2.800 Hz 2.800 Hz
Empfohlene Verstärkerleistung Recommended Amplifier Output	> 50 Watt(s) > 50 Watt(s)
Wirkungsgrad (2.8V/1m) Sensitivity	95 dB 95 dB
Ausführung Cabinet surface	schwarzer Teppich black carpet
Maße (BxHxT) Dimensions (WxHxD)	385 x 635 x 325 mm 385 x 635 x 325 mm
Gewicht Weight	19 Kg 19 kg

ART. NR.: 101 012

EAN: 40 18843 01012 0

Technische Daten/Specifications

Prinzip Principle	2 – Wege, Doppelbass Baßreflex 2 – way, bass reflex
Bestückung Equipment	2x 12“ (30 cm) Tief-Mitteltöner, 1.5“ DruckkammerHochtonhorn
Equipment	2x 12” woofer-midrange, 1.5” Compression-Horntweeter
Belastbarkeit (RMS/Max.) Power Handling (RMS/Max)	400 / 1000 Watt(s) 400 / 1000 Watt(s)
Impedanz Impedance	4-8 Ohm(s)
Frequenzbereich Frequency Response	26 – 22.000 Hz 26 – 22.000 Hz
Übergangsfrequenz Crossover Frequencies	2.800 Hz 2.800 Hz
Empfohlene Verstärkerleistung Recommended Amplifier Output	> 50 Watt(s) > 50 Watt(s)
Wirkungsgrad (2.8V/1m) Sensitivity	97 dB 97 dB
Ausführung Cabinet surface	schwarzer Teppich black carpet
Maße (BxHxT) Dimensions (WxHxD)	385 x 1005 x 390 mm 385 x 1005 x 390 mm
Gewicht Weight	30 Kg 30 kg

ART. NR.: 101 022

EAN: 40 18843 01022 9