

5.1 PACK BIRD - 5 BIRD & SUB AIR


Specification sheet

This Home Cinema pack which is composed of 5 Bird speakers and Sub Air perfectly represents the Bird line: offering the acoustic quality that flat-panel displays deserve. You no longer have to choose between audio and video quality. The light and compact satellites can be mounted to a wall or placed on your furniture according to your desire. The satellites will make you travel in a higher dimension: an amazing cinema experience at home! These 5 satellites are completed with the intense and deep sound of the Sub Air. Its wireless connection combined with its flatness make integration into interiors easy, removing all constraints due to cables. Having these veritable high-fidelity speakers as part of your 5.1 Home Cinema system will plunge you into the heart of the works of the seventh art.



Key points

- Real 2-way loudspeakers
- Focal design and technology, inspired by high-fidelity loudspeakers
- The ideal solution for rooms measuring 30 to 40m²
- Five similar loudspeakers, easy to install
- Trendy and compact: they can be mounted to a wall or ceiling, placed on a furniture or on an optional stand
- Sub Air: Install it anywhere thanks to its wireless connection (wireless transmitter included)
- Sub Air: High Gloss Piano Lacquered finish



	Bird
Type	Compact 2-way sealed speaker
Drivers	5 ^{1/2} " (14cm) Polyflex cone midbass Aluminum dome tweeter
Frequency response (±3dB)	70Hz–25kHz
Low frequency point (-6dB)	64Hz
Sensitivity (2.83V/1m)	89dB
Nominal impedance	8 Ohms
Minimum impedance	3 Ohms
Crossover frequency	2500Hz
Amplifier power	15-100W
Dimensions (H x W x D)	Tulipe: 11 ^{1/8} x6 ^{9/16} x7 ^{1/8} " (283 x 166 x 181mm) Cocotte: 10 ^{13/16} x8 ^{11/16} x8" (274 x 221 x 205mm)
Weight	4.63lb (2.1kg)

Type	SUB AIR, Flat bass-reflex subwoofer, integrated 150W BASH® amp
Speaker driver (diameter)	8" (21cm)
Bass cutoff frequency (-6dB)	35Hz
Frequency response (+/- 3dB)	40Hz-200Hz
Crossover cutoff frequency	Variable 50 Hz - 200 Hz
Input panel	Left Right / LFE
Continuous power output	110 W
Peak power	150 W
Phase adjustment	0 - 180° switch
Power functions	ON Auto (1 W) OFF (0,5 W)
Dimensions (HxWxD)	16.1"x14.2"x6.3" (410mmx360mmx160mm)
Weight	17 lbs (7.65 Kg)

Type	Wireless connection
Range in Meter	15 meters (in a room)
Sound Sampling	16 bits
Sampling Frequency	44,1kHz
Coding delay (latency)	13ms
Radio transmission powers or sensitivity	0dBm
Radio transmission frequency band	2,4Ghz ISM band