

5.1 PACK BIRD - 3 BIRD, 2 LITTLE BIRD & CUB³

Specification sheet

This Home Cinema pack which is composed of 3 Bird speakers and 2 Little Bird speakers perfectly represents the Bird line: offering the acoustic quality that flat-panel displays deserve. You no longer have to choose between audio and video quality. The light and compact satellites can be perched on the wall or on your furniture according to your desire. The satellites will make you travel in a higher dimension : an amazing cinema experience at home! There's no need to redesign your interior according to your sound system, your sound system can be easily and discretely integrated into your interior, reproducing the soundtracks of your favorite films with power and precision. Having these veritable high-fidelity speakers as part of your 5.1 Home Cinema system will plunge you into the heart of the works of the seventh art.



Key points

- Real 2-way loudspeakers
- Focal design and technology, inspired by high-fidelity loudspeakers
- The ideal solution for rooms measuring 20 to 30m²
- Trendy and compact: they can be mounted to a wall, ceiling, furniture or to an optional stand
- Discreet surround speakers for improved integration
- Cub3 subwoofer



	Bird	Little Bird
Type	Compact 2-way sealed speaker	Ultra compact 2-way sealed speaker
Drivers	5 1/2" (14cm) Polyflex cone midbass Aluminum dome tweeter	4" (10cm) Polyflex cone midbass Aluminum dome tweeter
Frequency response (±3dB)	70Hz–25kHz	89Hz – 25kHz
Low frequency point (-6dB)	64Hz	81Hz
Sensitivity (2.83V/1m)	89dB	87dB
Nominal impedance	8 Ohms	8 Ohms
Minimum impedance	3 Ohms	3.5 Ohms
Crossover frequency	2500Hz	2500 Hz
Amplifier power	15-100W	15 - 75 W
Dimensions (H x W x D)	Tulipe: 11 1/8x6 9/16x7 1/8" (283 x 166 x 181mm) Cocotte: 10 13/16x8 11/16x8" (274 x 221 x 205mm)	with Tulipe: 8x4 11/16x5 1/8" (202x119x130mm) with Cocotte: 7 11/16x6 1/4x5 13/16" (195x159x147mm)
Weight	4.63lb (2.1kg)	1.65lbs (0.75kg)

	Cub 3
Type	Compact bass-reflex active subwoofer, 150W BASH® built-in amplifier
Driver	8" (210mm)
L.F. (-6dB)	35Hz
Frequency response (+/- 3dB)	40Hz - 120Hz
Crossover frequency	120Hz
Inputs	line-in stereo/direct line-in (LFE)
Nominal power (RMS)	100W
Peak power	150W
Phase	0° / 180 °
Power function	on/off/standby
Dimensions (HxWxD)	13.1"x12"x12" (333mm x 300mm x 300mm)
Weight	24.2lbs(11kg)